

**PETRONAS**

TECHNICAL CHARACTERISTICS

TUTELA TRANSMISSION GI/E**PRODUCT CODE: 1505**

APPLICATION

Specific oil for hydraulic power steering, hydrostatic transmission, torque converter, automatic gear boxes.

SPECIFICATIONS

ATF DEXRON III G, FIAT 9.55550-AG2 CONTRACTUAL TECHNICAL REF. N°F001.C94,
IVECO 18-1807 CLASSE AG3/III, CONTRACTUAL TECHNICAL REF. N°I001.C06,
FORD MERCON (M- 011201), VOITH 55.6335.32, ZF TE-ML 04D, ZF TE-ML 09, ZF TE-ML 14A,
ZF TE-ML 17C, MAN 339 TYPE Z1 and V1 Performance, ALLISON C4 Performance,
MAN 339 TYPE Z2 and V2 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
COLOUR	--	--	RED
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,840
VISCOSITY AT 100°C	ASTM D445	cSt	7,6
VISCOSITY INDEX	ASTM D2270	--	180
FLASH POINT CI. O. C.	ASTM D92	°C	215
POUR POINT	ASTM D97	°C	-48

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT**09/2016**